

<p align="center">PHP Quick Ref Guide</p> <p>(C) 2005 Yves Aubry , www.netibu.com</p>	<p><i>"string"</i> : evaluated <i>'string'</i> : not evaluated</p>		
<p>File</p> <ul style="list-style-type: none"> •int <u>fopen</u> (string <i>path</i>, string <i>mode</i>) •string <u>fgets</u> (int <i>handle</i>) – one line reading •<u>fread</u> (int <i>handle</i>, string <i>chaine</i>, int <i>n</i>) •<u>fwrite</u> (int <i>handle</i>, string <i>chaine</i>) •<u>fprintf</u> (int <i>handle</i>, string <i>format</i>, var,...) •bool <u>fclose</u> (int <i>handle</i>) 	<p>String</p> <ul style="list-style-type: none"> •array <u>split</u> (string <i>pattern</i>, string <i>string</i>) •int <u>preg_match</u> (string <i>pattern</i>, string <i>string</i>) – return the number of match •int <u>substr</u> (string <i>string</i>, int <i>start</i>, int <i>length</i>) •int <u>strpos</u> (string <i>foin</i>, string <i>aiguille</i>) – return FALSE if not found 	<p>Display</p> <ul style="list-style-type: none"> •<u>echo</u> «string».«string».\$var •<u>print</u> <<< END <i>all this and multiple line are printed</i> END; – only this and no space 	<p>Time</p> <ul style="list-style-type: none"> •string <u>date</u> ("Y-m-d H:i:s") – now •string <u>date</u> ("Y-m-d H:i:s",int <i>tstamp</i>) •int <i>tstamp</i> <u>mktime</u> (H,m,s,Y,M,J,hiverI) •int <i>nowtstamp</i> <u>time</u> () – now in seconds •<u>sleep</u> (int <i>seconds</i>) •<u>usleep</u> (int <i>useconds</i>)
<p>Boucles</p> <ul style="list-style-type: none"> •<u>foreach</u> (array <i>array</i> as <i>valeur</i>) {...} •<u>foreach</u> (array <i>array</i> as <i>key</i> => <i>valeur</i>) {...} •<u>while</u> (<i>boolean expression</i>) {...} •<u>do</u> {...} <u>while</u> (<i>boolean expression</i>) ; •<u>break</u> – pour sortir d'une boucle 	<p>Test Type</p> <ul style="list-style-type: none"> •<u>is_numeric</u> (<i>var</i>) – t if number even in a string •<u>is_bool</u> (<i>var</i>) – t if boolean (true or false) •<u>is_float</u> (<i>var</i>) – t if float number •<u>is_int</u> (<i>var</i>) – t if integer •<u>is_string</u> (<i>var</i>) – t if string •<u>is_array</u> (<i>var</i>) – t if array •<u>is_object</u> (<i>var</i>) – t if array •<u>is_null</u> (<i>var</i>) – t if variable is NULL 	<p>Test</p> <ul style="list-style-type: none"> •if (<i>boolean expression</i>) { } else { } •<u>switch</u> (<i>var</i>) { <i>case val</i> : ; <u>break</u> ; <i>default</i> : ; } 	<p>String Protection</p> <ul style="list-style-type: none"> •string <u>addslashes</u> (string <i>str</i>) •string <u>stripslashes</u> (string <i>str</i>) •string <u>striptags</u> (string <i>str</i>,string <i>tagsOK</i>) •string <u>htmlspecialchars</u> (string <i>str</i>)
			<p>Divers</p> <ul style="list-style-type: none"> •<u>include</u> (string <i>filename</i>) – php include •<i>variable</i> <u>array</u>() ; – empty array creation •<i>variable</i> <u>array</u>('a','b',3) ; – array creation •<u>var_dump</u>(<i>variable</i>) ; – show content variable •<u>unset</u>(<i>variable</i>) ; – variable destruction